



THE TRIAD GROUP
700 W. North Shore Drive
Hartland, Wisconsin 53029
Phone: 262-538-2900
Fax: 262-538-2971
Emergency: 262-538-2900

ISSUE DATE: 25 JANUARY 2008

PRODUCT: Mineral Oil Enema

SECTION II: HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	%
---	-----------------	------------------	---------------------	----------

This is a food grade product! Not expected to present a significant hazard under anticipated conditions of use. Route of administration is ano-rectal. Not intended to be consumed by eating or drinking.

Mineral Oil, USP				100%
-------------------------	--	--	--	-------------

Oil Mist, Mineral (OSHA) 1989	5 mg/m ³			
--------------------------------------	---------------------	--	--	--

Oil Mist, Severely refined Mineral (ACGIH)	5 mg/m ³			
---	---------------------	--	--	--

SECTION III: PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: 600° F
Vapor Pressure (mm Hg.): @70° F 0.1 mm Hg
Vapor Density (AIR = 1): 10
Specific Gravity (H2O = 1): 0.86
Melting Point: NA
Evaporation Rate (Butyl Acetate = 1): NA
Solubility in Water: Not soluble in water
Appearance and Odor: Colorless and odorless liquid

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used): 410° F (D-92)

Flammable Limits: NA

LEL: NA

UEL: NA

Extinguishing Media: Water spray, dry chemical, CO2, inert gas – Halon/N2. Foam and water are effective, but may use frothing.

Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or confined fire space without protective equipment such as S.C.B.A.

Unusual Fire and Explosion Hazards: When heated above its flash point, this material will release flammable vapors which can burn in the open or be explosive in confined spaces if exposed to an ignition source. Keep away from heat and open flame

SECTION V: REACTIVITY DATA

Stability

Unstable: No

Stable: Yes

Conditions to Avoid: Keep away from heat and open flame

Incompatibility (Materials to Avoid): Strong acids and oxidizers such as liquid chlorine and oxygen

Hazardous Decomposition

or Byproducts: Burning or excessive heating may cause CO₂, CO, and other harmful substances.

Hazardous Polymerization

May Occur: No

Will Not Occur: Yes

Conditions to Avoid: Avoid extreme heat and open flame

SECTION VI: HEALTH HAZARD DATA

Route(s) of Entry

Inhalation? Possible

Skin? Possible

Ingestion? Possible

Health Hazards (Acute and Chronic): Not expected to cause adverse effects, but ingestion may cause irritation or laxative effect.

Carcinogenicity

NTP? NA

IARC Monographs? NA

OSHA Regulated? Mist only

Signs and Symptoms of Exposure: Ingestion may cause irritation or laxative effect.

Medical Conditions Generally

Aggravated by Exposure: None known

Emergency and First Aid Procedures: Remove from skin by wiping. If in eyes, flush with low-pressure clean water for at least 15 minutes.

SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case
Material is Released or Spilled: Contain spill and prevent from entering sewers or waterways. If possible, safely stop flow of spills.

Waste Disposal Method: Maximize product recovery for recycling. Spill material is biodegradable if exposed to microorganisms.

Precautions to Be Taken
in Handling and Storing: Keep container closed and avoid contamination. Avoid excessive heat or open flame.

SECTION VIII: CONTROL MEASURES

Respiratory Protection (Specify Type): None required under anticipated conditions of use.

Ventilation

Local Exhaust: NA
Mechanical
(General): NA
Special: NA
Other: NA

Protective Gloves: Optional – may be desired during application

Eye Protection: May be desired

Other Protective Clothing
or Equipment: As appropriate to conditions of use.